



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		S80LS			
MATERIAL		HOUSING-ABS			
		LENS-PC			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN		60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V ~ DC24V	5W	MAX. 0.160A
PROTECTION GRADE		WATER & DUST PROOF IP65			
CABLE ENTRY		Ø10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1	TITLE S80LS OUTLINE DRAWING		DWG. NO. S80LS_OUT				
	30~120	±0.15	±0.3	±0.8	±1.5				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							