



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			S80UK			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	5W	MAX. 0.484A	
			DC24V		MAX. 0.310A	
			AC110V		MAX. 0.080A	
			AC220V		MAX. 0.040A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø13 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6	±0.05	±0.1	±0.2	±0.5			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	6~30	±0.1	±0.2	±0.5	±1			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	30~120	±0.15	±0.3	±0.8	±1.5			TITLE			MODEL		
	120~400	±0.2	±0.5	±1.2	±2.5			S80UK			S80UK		
	400~1000	±0.3	±0.8	±2	±4			OUTLINE DRAWING			S80UK_OUT		
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°			DWG. NO.			S80UK_OUT		
	10~50	±0°30'		±1°	±2°			SCALE N/S			SIZE A4		
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

Qlight