



MARK	DATE	REVISION	REVISER	APP. BY
△				J.K.HAN
△				
△				

MODEL NO	SH8560-W/ SH8560S-W
MATERIAL	SH8560-W: HEAD & BODY - DIE CAST AL SH8560S-W: HEAD & BODY - DIE CAST BRASS
	BOLT,NUT,LEVER - SUS
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP56
CABLE ENTRY	PF 3/4"
COLOR	MAKER STANDARD
INSULATION RESISTANCE MIN.	at 500V DC

■ Operating Characteristics

OF max.g	2,300
RF min.g	1,800
PT	25°
MD max	15°
TT min	50°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-						
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QT'Y
	3~6	±0.05	±0.1	±0.2	-	DSND BY J.H.PARK		CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.06.25	
	6~30			±0.3	±0.5								
	30~120	±0.1	±0.2	±0.5	±1	TITLE SH8560/ SH8560S-W OUTLINE DRWAING		MODEL SH8560/ SH8560S-W					
	120~400	±0.15	±0.3	±0.8	±1.5				DWG. NO. SH8560/ SH8560S-W-OUT				
	400~1000	±0.2	±0.5	±1.2	±2.5					SCALE N/S	SIZE A4	REV 00	SHEET 1/1
FOR ANGULAR DIMENSIONS		±0.3	±0.8	±2	±4								
	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

