



MARK	DATE	REVISION	REVISER	APP. BY
1				J.K.HAN
2				
3				

MODEL NO	LZ1710-RL
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT,NUT,ROLLER,LEVER - SUS
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	EXPLOSION PROOF - Ex d IIC T6 WATER & DUST PROOF - IP67/ 68
CABLE ENTRY	STANDARD - M20
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

#### Operating Characteristics

OF max.g	1,300
RF min.g	210
PT	15°±5°
MD max.	5°
TT min.	70°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY J.H.PARK	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2018.03.15	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5	TITLE LZ1710-RL OUTLINE DRWAING			MODEL LZ1710-RL			
	120~400	±0.2	±0.5	±1.2	±2.5							
	400~1000	±0.3	±0.8	±2	±4							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. LZ1710-RL-OUT			
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0°10'		±0°13'	±0°30'							