



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			SEBAL			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED GLASS			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC24V	0.08W	MAX. 0.213A	
			AC110V		MAX. 0.131A	
			AC220V		MAX. 0.065A	
PROTECTION GRADE			WATER & DUST PROOF IP55			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO.7.5BG 7/2			
ACTION			LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2020.08.31
	6~30	±0.1	±0.2	±0.5	±1			TITLE SEBAL OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL SEBAL					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. SEBAL_OUT					
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			SCALE N/S SIZE A4 REV 00 SHEET 1/1					
	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

