



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SC1			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
			BRACKET-STEEL			
			HORN HOUSING-ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	10W	MAX. 1.288A	
			DC24V		MAX. 0.799A	
			AC110V		MAX. 0.203A	
			AC220V		MAX. 0.101A	
VOLUME		MAX. 108 dB				
PROTECTION GRADE		WATER & DUST PROOF IP44 (VARIOUS IP RATING AS PER CONFIGURATION)				
CABLE ENTRY		ø10 LEAD HOLE				
COLOR OF HOUSING		MAKER STANDARD				
ACTION		BULB REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-		
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.		TITLE/ NAME		MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30		
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.		SC1_OUT			
	10~50	±0°30'		±1°	±2°				SCALE N/S					SIZE A4
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									

A4(297X210)