



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO	SM400		
MATERIAL	HOUSING-STEEL/ ABS		
USE VOLT.	CURRENT	DC24V	12.000A
		AC110V	6.300A
		AC220V	3.800A
VOLUME	MAX. 123dB		
CABLE ENTRY	Ø22 LEAD HOLE		
COLOR	RED		
RATING	3 MIN.		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. SM400_OUT			
	10~50	±0°30'		±1°	±2°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							
	TITLE SM400 OUTLINE DRAWING											

**Qlight**