



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			S80DR		
MATERIAL			HOUSING-ABS		
			LENS-AS		
			REFLECTOR-HEAT RESISTING ABS		
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()		
REV. PER MIN.			120 ~ 140		
USE VOLT.	POWER LED	CURRENT	DC12V	1W	MAX. 0.183A
			DC24V		MAX. 0.127A
			AC110V		MAX. 0.035A
			AC220V		MAX. 0.017A
PROTECTION GRADE			WATER & DUST PROOF IP44		
CABLE ENTRY			ø10 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			POWER LED REVOLVING WARNING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-									
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE									
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30										
	3~6			±0.3	±0.5																
	6~30	±0.1	±0.2	±0.5	±1	TITLE S80DR OUTLINE DRAWING															
	30~120	±0.15	±0.3	±0.8	±1.5							MODEL S80DR									
	120~400	±0.2	±0.5	±1.2	±2.5																
400~1000	±0.3	±0.8	±2	±4	DWG. NO. S80DR_OUT																
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'							±3°										
	10~50	±0°30'		±1°							±2°										
	50~120	±0°20'		±0°30'							±1°							SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0°10'		±0°13'							±0°30'										

Qlight