



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			QA140HLSP			
MATERIAL			LENS-PC			
			HOUSING-PC			
			BRACKET-SUS			
COLOR OF LENS			RED(    ), AMBER(    )			
FLASHES PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	3W	MAX. 0.820A	
			DC24V		MAX. 0.600A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-						
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.10.05		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1	TITLE QA140HLSP OUTLINE DRAWING		MODEL QA140HLSP					
	30~120	±0.15	±0.3	±0.8	±1.5				DWG. NO. QA140HLSP_OUT				
	120~400	±0.2	±0.5	±1.2	±2.5					SCALE N/S	SIZE A4	REV 00	SHEET 1/1
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								