



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			SKTLBM		
MATERIAL			HOUSING-PC		
			LENS-PC		
			-		
COLOR OF LENS			RED(    ), AMBER(    )		
FLASHES. PER MIN			60 ~ 80		
USE VOLT.	LED	CURRNET	DC12V	3W	MAX.1.125V
			DC24V		MAX.0.560V
VOLUME			MAX. 105dB at 1m		
PROTECTION GRADE			WATER & DUST PROOF IP66		
CABLE ENTRY			ø9 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			LED STEADY / FLASHING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY Y.C.KO	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2018.09.20	
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1		TITLE  SKTLBM OUTLINE DRAWING		MODEL  SKTLBM				
	30~120	±0.15	±0.3	±0.8	±1.5					DWG. NO.  SKTLBM_OUT			
	120~400	±0.2	±0.5	±1.2	±2.5						SCALE N/S	SIZE A4	REV 00
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

A4(297X210)