



※ POWER CABLE : DC TYPE - UL2464 AWG22(0.3sq X 2C) 400mm
AC TYPE - VCTFK (0.75sq) x 2C 400mm

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		PSQELS			
MATERIAL		SIDE COVER : ABS			
		LENS-PC			
		BRACKET-SUS201			
COLOR OF LENS		UNCLEAR			
MODEL		PSQELS-200	PSQELS-300	PSQELS-400	PSQELS-500
CURRENT	DC24V	MAX. 0.145A	MAX. 0.215A	MAX. 0.285A	MAX. 0.358A
	AC110V	MAX. 0.196A	MAX. 0.202A	MAX. 0.206A	MAX. 0.216A
	AC220V	MAX. 0.095A	MAX. 0.098A	MAX. 0.100A	MAX. 0.105A
LED		CHIP LED			
PROTECTION GRADE		NON WATER-PROOF			

MODEL	A	B	C
PSQELS-200	249	200	16~170
PSQELS-300	349	300	16~270
PSQELS-400	449	400	16~370
PSQELS-500	549	500	16~470

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW
	3~6			±0.3	±0.5		S.H.KIM	J.H.PARK		J.K.HAN	3
	6~30	±0.1	±0.2	±0.5	±1						DATE
	30~120	±0.15	±0.3	±0.8	±1.5						2016.08.30
	120~400	±0.2	±0.5	±1.2	±2.5						
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4		TITLE PSQELS OUTLINE DRAWING			MODEL PSQELS	
	0~10	±1°		±1°30'	±3°					DWG. NO. PSQELS	
	10~50	±0°30'		±1°	±2°						
	50~120	±0°20'		±0°30'	±1°					SCALE N/S	SHEET 1/1
	120~400	±0°10'		±0°13'	±0°30'					SIZE A4	REV 00

A4(297X210)