


MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SKM/SKMH				
MATERIAL			HOUSING-PC				
			LENS-PC				
			REFLECTOR-PC/SUS				
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )				
REV. PER MIN.			120 ~ 140				
USE VOLT.	BULB	CURRENT	SKM	DC12V	15W	MAX. 1.544A	
				DC24V		MAX. 0.766A	
	SKMH	DC12V	35W	MAX. 3.077A			
		DC24V		MAX. 1.544A			
PROTECTION GRADE			WATER & DUST PROOF IP54				
CABLE ENTRY			φ10 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			BULB REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3			±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	±0.05	±0.1	±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			TITLE MSK/SKMH OUTLINE DRAWING 					
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			MODEL SKM/SKMH SKM/SKMH_OUT					
	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°			DWG. NO. SCALE N/S					
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'			SIZE A4	REV 00	SHEET 1/1			