



※ \*(198) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SH2				
MATERIAL			HOUSING-AL				
			LENS-PC				
			REFLECTOR-PC				
			PROTECTION CAGE-SUS316L				
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )				
REV. PER MIN			120 ~ 140				
USE VOLT.	BULB	CURRENT	DC12V		15W	MAX. 1.544A	
			DC24V			MAX. 0.766A	
			AC110V			MAX. 0.204A	
			AC220V			MAX. 0.102A	
PROTECTION GRADE			WATER & DUST PROOF IP66				
CABLE ENTRY			1/2" PF				
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2				
ACTION			BULB REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	⊙	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	<div>SH2 OUTLINE DRAWING</div> 				DWG. NO.		
	10~50	±0°30'		±1°	±2°					SH2_OUT		
	50~120	±0°20'		±0°30'	±1°					SCALE		
	120~400	±0°10'		±0°13'	±0°30'					N/S		
										SIZE		
										REV	SHEET	
										00	1/1	

A4(297X210)